

STAINLESS STEEL RAINSTOPPER

TECHNICAL DATA SHEET



RAINSTOPPER

Manhole Inflow & Infiltration Eliminated

CONSERVATIVE INFLOW COST-PER-DAY - 1 MANHOLE

- 12 gpm of inflow X 60 minutes = 720 gph
- 720 gph X 24 hrs = 17,280 gpd
- Total inflow per day/1,000 = 17.28
- 1-Day Tx cost (1000 gal) \$2 X 17.28 = \$34.56
- 10000 manholes @ 50 rainy days per year
\$17.28 million yearly
additional wastewater treatment costs
due to inflow only

IMMEDIATE ROI

30% avg reduction in TOTAL I & I
100% ROI



PRODUCT DESCRIPTION

The Stainless Steel Rainstopper is a patented manhole insert designed to eliminate inflow in your municipality's sanitary sewer system. It also reduces the infiltration of street level contaminants, while simultaneously controlling the escape of undesirable sewage odor and minimizing traffic related manhole noise and cover displacement. The insert is manufactured in the USA to precise, custom specifications from corrosion resistant 304 or 316 stainless steel. Its unique design allows the venting of sewer gases through a non-mechanical device, reducing maintenance costs by eliminating moving parts. Weighing only 10 pounds, it can be easily installed by a single person.

MANHOLE MEASUREMENT

Accurate frame and cover measurements are absolutely critical for the successful elimination of inflow. While carefully following the instructions included on the Rainstopper Measurement Worksheet, measure and record the physical dimensions for each unique manhole frame and cover. Enter the desired quality for each measurement configuration. Do not hesitate to contact us at the number listed below if you have questions or concerns.

ACCEPTANCE AND STORAGE

Long term exposure to UV rays can deteriorate the gasket, so care should be taken to protect the stored units prior to installation. Manufacturer recommends either leaving polyethylene shrink wrapped units on pallets if stored outside or storing unpackaged units in an area protected from direct sunlight.

INSTALLATION

To install the Rainstopper, remove the manhole lid. Clean all dirt and debris from manhole frame. Seat Rainstopper in manhole frame rim. Replace manhole lid. Ensure lid is flush with frame to alleviate tripping hazard. Once installed, maintenance is not required.

WARRANTY

Limited fifteen-year replacement warranty: If insert is defective in materials or workmanship within fifteen years of purchase, it will be replaced free of charge by Rainstopper if not damaged through mishandling, accident, or abnormal use, and excludes replacement of handle, valve, and gasket.

